


# APE HOLLAND



## MODEL 150 TUNGSTEN VIBRATORY DRIVER / EXTRACTOR

- \* Rifle-bored top plate delivers oil to motors without using hoses
- \* Patented one piece helical gear/eccentric eliminates gearbox failures caused by broken pins, keys, bolts or splines found in all other vibro gearboxes
- \* Giant double roller spherical bearings for super long life
- \* Center safety pin shows the line load on pile and cranes



**SPECIFICATIONS:**

**Model 150T**

Eccentric moment	30 kg-m
Frequency (variable)	0 - 1.800 vpm (0 - 30 Hz)
Centrifugal force	1.063 kN
Amplitude	20 mm
Maximum line pull	711 kN (72,5 ton)
Eccentric mass	372 kg
Dynamic mass	1.905 kg
Suspended weight	3.900 kg
Length	223 cm
Width	36 cm
Height (with clamp attachment)	180 cm
Hydraulic Hose Length (standard)	30 meters
Extra hose length available in 15 meter (50 foot) sections.	

**SPECIFICATIONS**

**Model 375**

Engine	CAT C9
Maximum power	375 hp (279 kW)
Make of Pumps	Parker
Maximum drive pressure	330 bar
Maximum hyd. flow	475 lpm
Clamp pressure	350 bar
Clamp pump flow	40 lpm
Weight	5.800 kg
Length	325 cm
Width	186 cm
Height	170 cm
Fuel capacity	460 liters
Hydraulic tank capacity (main)	1000 liters
Hydraulic tank capacity (reserve)	200 liters



Advanced, profit generating features of the APE equipment:

- \* *Vibro will not shake the crane line or boom even during vibro "starting" and "stopping."*
- \* *Heavy metal enhanced eccentrics eliminates 50% of the parts. Patented two-stage suppressor has twice the line pull of any vibro on the market.*
- \* *Center safety pin shows pile crew and crane operator how much line pull is on pile and crane.*
- \* *Only vibro on market with detachable suppressor housings to fit any height and weight requirements.*
- \* *One piece helical gear/eccentric eliminates keyways, pins, splines, and bolts inside the gearbox.*
- \* *Heavy metal enhanced eccentric design reduces internal parts by up to 75% while increasing dynamic force.*
- \* *Giant spherical bearings allow for batter operations without damage and reduce heat for extremely long life.*
- \* *Computer designed gearbox is perfectly balanced with lowest center of gravity on the market.*
- \* *Rifle bored top plate eliminates all hoses on suppressor and to hydraulic motors.*
- \* *Heavy duty clamp cylinder is machined from one piece of solid steel to eliminate o-rings and bolt-on guards.*
- \* *Power unit comes standard with spare hydraulic tank, tool kit, dual controls on pendant and control panel.*
- \* *Very simple open loop hydraulic system with highest quality valves with lighted indicators.*
- \* *Oversized radiator and hydraulic oil cooler with proven performance in the heat of Saudi Arabia.*
- \* *Engines comply to TIER III standards.*

APE Holland BV, P.O. Box 34, 7990 AA Dwingeloo, The Netherlands

Tel.: +31(0) 593 54 08 91, Fax: +31(0) 593 54 27 84, [www.apeholland.com](http://www.apeholland.com), [info@apeholland.com](mailto:info@apeholland.com)

Due to constant improvements we must advise you to call APE Holland for the latest available literature and specifications. 06/06

APE HOLLAND